



THE NEW DIAMOND. MATCHING FACEPLATE.



D SERIES

The new Diamond! Fresh design, built-in USB ports, same faceplate.

Teledex D Series

- Single and Two-Line Telephone
- Optional USB charging ports (2)*
- Optional Speakerphone – Hands-free conversations*
- Patented OneTouch voice mail retrieval*
- Guest Service Keys – Up to ten for access to hotel services
- Hidden Programming Key – Eliminates arbitrary reprogramming of autodial keys
- ADA Handset Volume Boost – Three (3) distinct levels, compliant with HAC/VC and FCC requirements
- Raised Red Message-Waiting Lens – Easily seen from any area in the guestroom
- Message-Waiting Circuitry – Message Waiting will activate on high or low voltage; Guarantees operation of up to 7 phones for suite applications, with an extra-bright message-waiting lamp
- Mute Key – Deactivates microphone during speakerphone and handset calls; a red LED indicates activation**
- Speaker On/Off Key – With red LED for easy speakerphone activation*

- Electronic 3-way Call Conference Function with LED indicator for convenient multi-line conversations***
- Hold Key – Places the active line on hold so the second line can be used or a conference call initiated***
- Hold Release Detection Circuit – Releases calls on hold when line is accessed by any telephone
- Redial Key – Automatically redials the last number dialed (most models)
- Flash Key (most models)
- Textured Finish – Provides durable resistance against scratches and smudges
- Full-Length Paper Faceplate – Allows user-friendly customization
- Desk or Wall Mountable – Provides placement flexibility
- Available in Ash or Black

*Speakerphone models only

**Not available in single-line basic or lobby phone

***Two-line only

TELEDEX D SERIES

SPECIFICATIONS

Standard Color:	Ash and Black
Footprint (Desk):	6.25" (15.88cm) (w) x 9.5" (24.13cm) (l) x 2.5" (6.35cm) (d) (without handset); 6.25" (15.88cm) (w) x 9.5" (24.13cm) (l) x 3.75" (9.53cm) (d) (with handset)
Footprint (Wall):	6.25" (15.88cm) (w) x 9.5" (24.13cm) (l) x 2.13" (5.41cm) (d) (without handset); 6.25" (15.88cm) (w) x 9.5" (24.13cm) (l) x 3.25" (8.23cm) (d) (with handset)
Weight:	1.90 lbs. (0.86kg)
Packaging:	10 per carton
Faceplate Size:	3.13" (w) x 8.75" (l)
FCC Specifications:	Meet or exceeds Part 15, Subpart J, Class A, Part 68
Safety Standard:	ETL and CE
Operating Voltage:	24 to 56 VDC Non-Polarity

Signaling:	Standard 12 tone DTMF no Pulse/Rotary dialing
Flash Timing:	100 mS to 1000 mS
Ringer Equivalence:	Z
Cabling:	2 pair minimum
Registered Connector:	USOC RJ-14
Handset:	Hearing Aid compatible Standard "K" type
Handset Cord:	10-foot coil cord
Line Cord:	12-foot, 2 pair
Optional USB Charging Ports:	Power Supply: Input 100 – 240V @ 50/60Hz, Output 5V @ 4A. USB output: 2 type A, Output 5V @ 2A

PART NUMBERS

D100 Lobby – 1L, 0GSK

DA210N0L	Ash
DA110N0L	Black

D100 Basic – 1L, 0GSK

DA210N0D	Ash
DA110N0D	Black

D1003 – 1L, 3 GSK

DA210N3D	Ash
DA110N3D	Black

D1005 – 1L, 5 GSK

DA210N5D	Ash
DA110N5D	Black

D10010 – 1L, 10 GSK

DA210N10D	Ash
DA110N10D	Black

D100S3 – 1L, 3 GSK, Speakerphone

DA210S3D	Ash
DA110S3D	Black

D100S5 – 1L, 5 GSK, Speakerphone

DA210S5D	Ash
DA110S5D	Black

D100S10 – 1L, 10 GSK, Speakerphone

DA210S10D	Ash
DA110S10D	Black

D200L2E – 2L, 0GSK

DA220N0D	Ash
DA120N0D	Black

D200L25E – 2L, 5 GSK

DA220N5D	Ash
DA120N5D	Black

D200L210E – 2L, 10 GSK

DA220N10D	Ash
DA120N10D	Black

D200L255E – 2L, 5 GSK, Speakerphone

DA220S5D	Ash
DA120S5D	Black

D200L2S10E – 2L, 10 GSK, Speakerphone

DA220S10D	Ash
DA120S10D	Black

D100S3U – 1L, 3 GSK, Speakerphone, USB

DA210S3DU	Ash
DA110S3DU	Black

D100S5U – 1L, 5 GSK, Speakerphone, USB

DA210S5DU	Ash
DA110S5DU	Black

D100S10U – 1L, 10 GSK, Speakerphone, USB

DA210S10DU	Ash
DA110S10DU	Black

D200S5U – 2L, 5 GSK, Speakerphone, USB

DA220S5DU	Ash
DA120S5DU	Black

D200S10U – 2L, 10 GSK, Speakerphone, USB

DA220S10DU	Ash
DA120S10DU	Black

U.S. Toll Free 1 800 794 8353

Telephone +1 719 638 8821

Fax +1 719 638 8815

info@teledex.com

teledex.com