



**NOW WITH BUILT-IN USB  
CHARGING PORTS.**



## E SERIES USB

USB ports in analog, VoIP, corded, cordless configurations.

# E SERIES USB

Guests are bringing an average of 4 to 5 smart devices into the room. Are you ready? E Series USB hotel phones are equipped with USB charging ports on both analog and VoIP models to help facilitate guest smart device charging and keep them connected. Originally designed to meet the limited space requirements aboard cruise ships, E Series USB phones also require less room on the hotel guestroom desk and nightstand, and consume less energy in the manufacturing process, so the impact on the environment is smaller as well.

Small is the new big.



## E Series USB Analog Cordless

- Available frequencies: 1.8 GHz and 1.9 GHz
- Single or two-line speakerphones
- 2 side USB power ports for device charging
- Handset kit has 2 USB power ports for device charging
- 4 or 8 configurable guest service keys
- Patented OneTouch voice mail retrieval
- Supports up to four handsets, including one on the base and three remotes
- Dual Neon/LED message-waiting light
- HAC/VCH (ADA) compliant handset volume boost
- Electronic 3-way conference (2-line only)
- RediDock available
- HAC/VCH (ADA) compliant handset volume boost
- Full-length customizable paper faceplate
- Available in Black

## E Series USB VoIP Cordless

- Available frequencies: 1.8 GHz and 1.9 GHz
- Single or two-line speakerphones
- 1 side USB power port for device charging
- Handset kit has 2 USB power ports for device charging
- 4 or 7 configurable guest service keys
- Patented OneTouch voice mail retrieval
- Supports up to four handsets, including one on the base and three remotes
- Dual Neon/LED message-waiting light
- HAC/VCH (ADA) compliant handset volume boost
- Electronic 3-way conference (2-line only)
- Dual Port (10/100) for HSIA
- RediDock available
- HAC/VCH (ADA) compliant handset volume boost
- Full-length customizable paper faceplate
- Available in Black

## E Series USB Analog Corded

- Single or two-line speakerphones
- 2 side USB power ports for device charging
- 4 or 8 configurable guest service keys
- Patented OneTouch voice mail retrieval
- Dual Neon/LED message-waiting light
- Electronic 3-way conference (2-line only)
- ETrim available
- HAC/VCH (ADA) compliant handset volume boost
- Full-length customizable paper faceplate
- Available in Black

## E Series USB VoIP Corded

- LCD display with digital clock screen
- Single or two-line speakerphones
- 1 side USB power port for device charging
- 4 or 7 configurable guest service keys
- Patented OneTouch voice mail retrieval
- Dual Neon/LED message-waiting light
- Electronic 3-way conference (2-line only)
- Dual Port (10/100) for HSIA
- ETrim available
- HAC/VCH (ADA) compliant handset volume boost
- Full-length customizable paper faceplate
- Available in Black

# E SERIES USB VoIP

## SPECIFICATIONS

**Standard Color:** ..... Black  
**Footprint (Desk):** ..... 4.5" (11.43cm) (w) x 8" (20.32cm) (l) x 3.63" (9.22cm) (d) (max height with desk stand)  
**Footprint (Wall):** ..... 4.5" (11.43cm) (w) x 8" (20.32cm) (l) x 1.5" (3.81cm) (d) (depth from wall mount)  
**Footprint (RediDock):** ..... Same as above  
**Weight:** ..... 2.3 lbs. (1.04 kg)  
**Weight (Redidock):** ..... 1.05 lbs. (0.48 kg)  
**Frequency:** ..... 1.9 GHz or 1.8 GHz  
**Power:** ..... Power over Ethernet (POE) 802.3af Compliant  
**Power (Cordless):** ..... Remote Charging Station includes Handset with Battery & A/C adaptor  
**Standby Time (Cordless):** ..... 10 days

**Talk Time (Cordless):** ..... 6 hours  
**Range (Cordless):** ..... 100ft (30m)  
**Humidity:** ..... 65% ± 20%  
**Temperature:** ..... 77°F ± 50° (25°C ± 10°C)  
**Packaging:** ..... 10 per carton  
**Packaging (RediDock):** ..... 20 per carton  
**Faceplate Size:** ..... Full length  
**FCC Specifications:** ..... FCC Part 15 Subpart B: 2009  
**Safety Standard:** ..... UL - 60950-1 2nd edition  
..... ADA/HAC  
**Handset:** ..... 10 ft (3.048m)  
**Line Cord:** ..... RJ14 line cord - 12 ft (3.66m)  
**Line Cord (Cordless):** ..... RJ45 line cord - 12 ft (3.66m)

RFCs: 3261 (SIP), 3842 (SIP Subscribe), 2833 (SIP Info)

## PART NUMBERS

### SINGLE-LINE VoIP USB CORDED

#### E100IP - Lobby

EV10N0L3 ..... Black

#### E100IP - 4 GSK

EV110S4DU3 ..... Black

#### E100IP - 7 GSK

EV110S7DU3 ..... Black

#### E100IP - ETrim

EV110N0T3 ..... Black

### TWO-LINE VoIP USB CORDED

#### E200IP - 4 GSK

EV120S4DU3 ..... Black

#### E200IP - 7GSK

EV120S7DU3 ..... Black

#### E200IP - ETrim

EV120N0T3 ..... Black

### SINGLE-LINE VoIP USB CORDLESS

#### E103IP - 4 GSK

EV11319S4DU3 ..... Black

#### E103IP - 7 GSK

EV11319S7DU3 ..... Black

#### E103IP - RediDock

EV11319S0HKU3 ..... Black

### TWO-LINE VoIP USB CORDLESS

#### E203IP - 4 GSK

EV12319S4DU3 ..... Black

#### E203IP - 7 GSK

EV12319S7DU3 ..... Black

#### E203IP - RediDock

EV12319S0HKU3 ..... Black

# E SERIES USB ANALOG

## SPECIFICATIONS

**Standard Color:** ..... Black  
**Footprint (Desk):** ..... 4.5" (11.43cm) (w) x 8" (20.32cm) (l) x 3.63" (9.22cm) (d) (max height with desk stand)  
**Footprint (Wall):** ..... 4.5" (11.43cm) (w) x 8" (20.32cm) (l) x 1.5" (3.81cm) (d) (depth from wall mount)  
**Footprint (RediDock):** ..... Same as above  
**Weight:** ..... 1.7 lbs. (0.77 kg)  
**Weight (Redidock):** ..... 0.93 lbs. (0.42 kg)  
**Frequency:** ..... 1.9 GHz or 1.8 GHz  
**Power:** ..... Adapter  
**Power (Cordless):** ..... Remote Charging Station includes Handset with Battery & A/C adaptor  
**Standby Time (Cordless):** ..... 10 days  
**Talk Time (Cordless):** ..... 6 hours  
**Range (Cordless):** ..... 100ft (30m)

**Humidity:** ..... 65% ± 20%  
**Temperature:** ..... 77°F ± 50° (25°C ± 10°C)  
**Packaging:** ..... 10 per carton  
**Packaging (RediDock):** ..... 20 per carton  
**Faceplate Size:** ..... Full length  
**FCC Specifications:** ..... Meets or exceeds Part 68, FCC Part 15 & UL 1459 Ref.  
**Safety Standard:** ..... UL - 60950-1 2nd edition  
..... ADA/HAC  
**Operating Voltage:** ..... 24 to 56 VDC Non-Polarity  
**Flash Timing:** ..... 600 ms  
**Ringer Equivalence:** ..... Z (Use only behind PBX)  
**Handset:** ..... 10 ft (3.048m)  
**Line Cord:** ..... RJ14 line cord - 12 ft (3.66m)  
**Line Cord (Cordless):** ..... RJ45 line cord - 12 ft (3.66m)

## PART NUMBERS

### SINGLE-LINE ANALOG USB CORDED

#### E100 - Lobby

EA011000N00L ..... Black

#### E100 - 4 GSK

EA110S4DU ..... Black

#### E100 - 8 GSK

EA110S8DU ..... Black

#### E100 - ETrim

EA110N0T ..... Black

### TWO-LINE ANALOG USB CORDED

#### E200 - 4 GSK

EA120S4DU ..... Black

#### E200 - 8 GSK

EA120S8DU ..... Black

#### E200 - ETrim

EA120N0T ..... Black

### SINGLE-LINE ANALOG USB CORDLESS

#### E103 - 4 GSK

EA11319S4DU ..... Black

#### E103 - 8 GSK

EA11319S8DU ..... Black

#### E103 - RediDock

EA11319S0HKU ..... Black

### TWO-LINE ANALOG USB CORDLESS

#### E203 - 4 GSK

EA12319S4DU ..... Black

#### E203 - 8 GSK

EA12319S8DU ..... Black

#### E203 - RediDock

EA12319S0HKU ..... Black



U.S. Toll Free 1 800 794 8353  
Telephone +1 217 239 6533  
Fax +1 719 638 8757

[info@teledex.com](mailto:info@teledex.com)  
[teledex.com](http://teledex.com)