

TELEDEX®

**DESIGNED WITH
THE WORLD IN MIND.**



OPAL SERIES

Soft curves, legendary quality.



INTERNATIONAL DESIGN

The Teledex Opal Series combines stylish international design with legendary Teledex reliability, in a package that helps any property put its best foot forward.

Opal DCT 1900/2900/1800/2800 Series

- 1.9 and 1.8 GHz DECT Technology for best range, clarity, & security
- Single or Two line configuration
- EZ-Answer connects to incoming call by pressing any key
- Superior Quality Speakerphone for convenient Hands-free calls
- Two lines with conference*
- Supports up to five handsets, including one on the base and four remotes
- AutoSync – handset automatically syncs with base unit when in cradle
- Optional remote cordless handset battery backup
- Easy-access data port
- Up to ten Configurable Guest Service Keys
- LifeLinePlus allows use during power failure
- Last number redial
- Lighted handset keypad
- Handset page/locator
- Low battery indicator
- Breakage-resistant, non-extending antenna
- Large printable faceplate area
- Line status indicators*
- Bright message wait lamp and positive charge indicator
- 5-Year Warranty

**Two-line only*



Opal 1000/2000 Series Analog

- Single or Two line configuration
- Optional speakerphone
- Auto Detect MWI for high and low voltage signaling
- Large printable faceplate area for important dialing and contact information
- Easy-access data port for convenient laptop computer connection
- Sleek Euro design complements any room decor
- Extra-bright message waiting indicator
- Electronic 3-way conference*
- Last-number redial
- Up to 11 Configurable Guest Service Keys
- Handset volume boost
- 5-Year Warranty

**Two-line only*



Opal Trimline Analog Series

- Single or Two line configuration
- Optional message waiting indicator
- ADA-compliant volume control
- Flash, Redial, Mute keys
- 5-Year Warranty



OPAL DCT 1900/2900/1800/2800 SERIES

SPECIFICATIONS

Standard Color: Ash and Black
Footprint (Desk):
 6.0" (15.24cm) (w) x 9.0" (22.86cm) (l) x 2.13" (5.41cm) (d) (without handset);
 6.0" (15.24cm) (w) x 9.0" (22.86cm) (l) x 3.38" (8.59cm) (d) (with handset)
Footprint (Wall):
 6.0" (15.24cm) (w) x 9.0" (22.86cm) (l) x 1.75" (4.45cm) (d) (without handset);
 6.0" (15.24cm) (w) x 9.0" (22.86cm) (l) x 3.0" (7.62cm) (d) (with handset)
Footprint (RediDock): 3.75" (w) x 8.17" (l) x 3.38" (d) (9.53cm x 20.75cm x 8.59cm)
Weight: 2.0 lbs. (0.9kg)
Weight (Redidock): 7 oz. (0.2kg) (without handset)
 0.95 lbs. (0.43kg) (with handset)
Frequency: 1.9 GHz or 1.8 GHz
Power: 9 VDC adapter
Standby Time: 14 days

Talk Time: 4 hours
Humidity: 65% ± 20%
Temperature: 77°F ± 50° (25°C ± 10°C)
Packaging: 10 per carton
Packaging (RediDock): 20 per carton
Faceplate Size: Full length
FCC Specifications: Meet or exceeds Part 15, Subpart J, Class A, Part 68
Safety Standard: ETL and CE
Operating Voltage: 24 to 56 VDC Non-Polarity
Flash Timing: 600 ms
Ringer Equivalence: Z (Use only behind PBX)
Handset: Hearing Aid compatible
Line Cord: 12-foot, 2 RJ45

PART NUMBERS

DECT 1.9 GHZ (SINGLE LINE)

Opal DCT1905

OPL95149 Ash
 OPL951491 Black

Opal DCT1910

OPL95339 Ash
 OPL953391 Black

RediDock

RD1910 (Single-line)

OPL95339HDKIT Ash
 OPL953391HDKIT Black

DECT 1.9 GHZ (TWO LINE)

Opal DCT2905

OPL97149 Ash
 OPL971491 Black

Opal DCT2910

OPL97359 Ash
 OPL973591 Black

RediDock

RD2910 (Two-line)

OPL97359HDKIT Ash
 OPL973591HDKIT Black

DECT 1.8 GHZ (SINGLE LINE)

Opal DCT1805

OPL95148 Ash
 OPL951481 Black

Opal DCT1810

OPL95338 Ash
 OPL953381 Black

RediDock

RD1910 (Single-line)

OPL95338HDKIT Ash
 OPL953381HDKIT Black

DECT 1.8 GHZ (TWO LINE)

Opal DCT2805

OPL97148 Ash
 OPL971481 Black

Opal DCT2810

OPL97358 Ash
 OPL973581 Black

RediDock

RD2810 (Single-line)

OPL97358HDKIT Ash
 OPL973581HDKIT Black

OPAL 1000/2000 SERIES ANALOG

SPECIFICATIONS

Standard Color: Ash and Black
Footprint (Desk):
 6.0" (15.24cm) (w) x 9.0" (22.86cm) (l) x 2.13" (5.41cm) (d) (without handset);
 6.0" (15.24cm) (w) x 9.0" (22.86cm) (l) x 3.38" (8.59cm) (d) (with handset)
Footprint (Wall):
 6.0" (15.24cm) (w) x 9.0" (22.86cm) (l) x 1.75" (4.45cm) (d) (without handset);
 6.0" (15.24cm) (w) x 9.0" (22.86cm) (l) x 3.0" (7.62cm) (d) (with handset)
Weight: 2.0 lbs. (0.9kg)
Humidity: 65% ± 20%
Temperature: 77°F ± 50° (25°C ± 10°C)
Packaging: 10 per carton

Faceplate Size: Full length
FCC Specifications: Meet or exceeds Part 15, Subpart J, Class A, Part 68
Safety Standard: ETL and CE
Operating Voltage: 24 to 56 VDC Non-Polarity
Flash Timing: 600 ms
Ringer Equivalence: Z (Use only behind PBX)
Registered Connector: USOC RJ-14
Handset: Hearing Aid compatible
Handset Cord: 10-foot coil cord
Cords & Line: 12-foot/10-foot coil

PART NUMBERS

SINGLE-LINE MODELS

Opal 1001 (Basic)

OPL76009 Ash
 OPL760091 Black

Opal 1000 (Basic)

OPL76309 Ash
 OPL763091 Black

Opal 1002 (Basic)

OPL76039 Ash
 OPL760391 Black

Opal 1003 (3-button)

OPL76739 Ash
 OPL767391 Black

Opal 1005 (5-button)

OPL76139 Ash
 OPL761391 Black

Opal 1010 (10-button)

OPL76239 Ash
 OPL762391 Black

Opal 1003s (3-button speaker)

OPL76749 Ash
 OPL767491 Black

Opal 1005s (5-button speaker)

OPL76149 Ash
 OPL761491 Black

Opal 1010s (10-button speaker)

OPL76339 Ash
 OPL763391 Black

TWO-LINE MODELS

Opal 2006 (6-button)

OPL78039 Ash
 OPL780391 Black

Opal 2011 (11-button)

OPL78259 Ash
 OPL782591 Black

Opal 2006s (6-button speaker)

OPL78149 Ash
 OPL781491 Black

Opal 2011s (11-button speaker)

OPL78359 Ash
 OPL783591 Black

OPAL TRIMLINE ANALOG SERIES

SPECIFICATIONS

Standard Color: Ash and Black
Footprint (Desk, Wall):
 3.75" (9.53cm) (w) x 8.17" (20.75cm) (l) x 2.0" (5.08cm) (l) (without handset);
 3.75" (9.53cm) (w) x 8.17" (20.75cm) (l) x 3.38" (8.59cm) (l) (with handset)
Weight: 0.95 lbs. (0.43kg)
Power: Line
Humidity: 65% ± 20%
Temperature: 77°F ± 50° (25°C ± 10°C)

Packaging: 20 per carton
FCC Specifications: Meet or exceeds Part 15, Subpart J, Class A, Part 68
Safety Standard: ETL and CE
Operating Voltage: 24 to 56 VDC Non-Polarity
Ringer Equivalence: Z (Use only behind PBX)
Registered Connector: USOC RJ-14
Handset: ADA-compliant
Cords & Line: 12-foot/10-foot coil

PART NUMBERS

OPAL TRIMLINE (SINGLE-LINE)

NO MWL

OPL69019 Ash
 OPL690191 Black

With MWL

OPL69119 Ash
 OPL691191 Black

OPAL TRIMLINE 2 (TWO-LINE)

NO MWL

OPL69059 Ash
 OPL690591 Black

With MWL

OPL69159 Ash
 OPL691591 Black



U.S. Toll Free 1 800 794 8353
Telephone +1 719 638 8821
Fax +1 719 638 8815

info@teledex.com
teledex.com

© 2018 Cetus, Inc. Product specifications and descriptions in this document subject to change without notice.
Cetus®, TeleDEX®, TeleMatrix®, and Scitec® are trademarks or registered trademarks of Cetus, Inc.

TDX-0-DS-082018