

WAVE-FORM DESIGN. SIZZLING PERFORMANCE.

A bold new merger of European design and American engineering.

C SERIES

SIP corded Telephones



C Series

Cetis 

Scitec • Teledex • TeleMatrix

CetisGroup.com

C SERIES

The power and flexibility of SIP.

Our stunning new C Series SIP endpoints with optional color accent panels are designed to meet your most demanding phone system requirements and office décor preferences. Equipped with twelve feature/line keys with busy lamp fields, patented One-Touch™ message retrieval, optional color accent panels, and a wide view backlit LCD Type II caller ID screen.

Features

- Single and Two line configurations
- Deluxe LCD Display Speakerphone
- SIP 2.0 Compatible (field upgradable)
- Eleven (M1-M11) Programmable Speed Dial/Function Keys
- Single Line Configuration
- Redial, Mute, & Hold Feature Keys
- Soft Key Technology
- Dual-Port 10/100Mb Switched Ethernet Ports for Laptop
- High Speed Internet connection
- On-Hook Pre-Dialing on Memory Keys
- Industrial Grade Construction with Matte Finish Design
- Non-Slip Base

Network Features

- Dual-Port 10/100Mb switched Ethernet Ports for HSIA
- Supports IEEE 8.2.1 pg for Quality of Service/VLAN Priority Tagging, 2.5W = Class 1 - Accepts Standard Based (IEEE 802.3 aq)
- Power over Ethernet
- Compression Support G.711, G.729
- Encryption 128-bit AES
- RCF 3261 SIP 2.0
- SIP Trunkside Integration



Audio/Visual Features

- Wide-View Backlit LCD Screen Display
- Exceptional Quality Speakerphone
- Built-In Headset Amplifier
- Large, Bright Red, Message Waiting Lamp
- Multi Step Speaker, Headset and Handset Volume Control
- Three Way Conference Calling*
- Headset On/Off key
- One-Touch™ Message Retrieval
- Memory Key Entry - Maximum 30 Digits
- Sixteen (16) Pre-defined hard and LCD control keys: Up, Down, SYS/IP, Enter, Exit, Menu, Del (delete), Call Log, FWD (forward), Redial, Phone book, Hold, DND, Mute, Headset on/off, Speaker
- Language Selections - English

Standard warranty applies (www.CetisGroup.com)

**Two-line models only*

Specifications:

Standard Color: Black and Gray
Footprint: 6.75" x 8.5" (12.25cm x 16.87cm)
Weight: 2.0 lbs. (0.9kg)
Power: Local or PoE (Optional)
Humidity: 65% ± 20%
Temperature: 77°F ± 50° (25°C ± 10°C)
Packaging: 10 per carton
FCC Specifications: Meets or exceeds Part 15, UL 1459 Ref., Subpart J, Class A, Part 68
Safety Standard: ETL and CE

Operating Voltage: 24 to 56 VDC Non-Polarity
Flash Timing:600 ms
Ringer Equivalence: Z (Use only behind PBX)
Registered Connector: USOC RJ-14
Handset: ADA/FCC Hearing Aid Compatible
Cords & Line: 15-foot RJ45/9-foot coil

Cetis, Inc. Worldwide Headquarters

5025 Galley Road, Colorado Springs, CO 80915

North America Toll Free 1 800 462 9446 • Telephone +1 719 638 8821 • Fax +1 719 638 8815 • info@cetisgroup.com • cetisgroup.com



Scitec • Teledex • TeleMatrix