

REMARKABLE DESIGN. RICH FEATURE SET.

A bold new merger of European design and American engineering.

R SERIES

Single and two line speakerphone
Analog corded Telephones



R100
single-line 11 button Gray

Cetus 

Scitec • Teledex • TeleMatrix

CetusGroup.com

R SERIES

Single and two line speakerphone with 11 programmable feature keys.

R Series telephones deliver a rich call feature suite in a dazzling new angular pedestal footprint. Choose single or two-line Type II Caller ID or non-caller ID configuration with up to 11 programmable feature/line keys and patented OneTouch™ voice mail retrieval.

Features

- Single and Two line, Caller ID speakerphone
- 11 programmable feature keys
- Line-powered, requires no batteries
- 12 phones per case

Design

- Contemporary feature phone styling
- Long wearing engraved keys
- Non-marring, non-slip silicon feet
- Available in Black and Gray
- Custom colors available (with minimum order)
- Desk or wall mountable

Volume/Ringer

- 3-step volume control
- ADA-compliant volume control
- Electronic ringer
- HI/LO/OFF ringer control

Feature Keys

- Volume control key
- Hands-free speaker key
- Up/Down Caller ID toggle bar
- Caller ID delete and dial keys
- Adjustable flash and pause time keys
- Redial key
- Mute key
- Programmable hold key for local hold or PBX hold



Operation

- 11 programmable speed dial keys
- Line-powered, requires no AC adaptor or batteries to operate or maintain programming functions
- Migrates to IP switch applications
- Supports both Type I (on-hook) and Type II (call waiting) Caller ID
- Type II Caller ID may be disabled
- Retains up to 60 messages in memory
- Area code and up to 15 characters
- maybe programmed in display
- Message waiting light provides user notification of voice mail messages
- Side-mounted dataport provides access for laptops and other devices

Specifications:

| | |
|-----------------------|--------------------------------------------------------------|
| Standard Colour: | Gray and Black |
| Footprint: | 8.5" (12.25cm) (l) x 6.75" (16.87cm) (w) x 3.5" (8.75cm) (h) |
| Weight: | 2.0 lbs. (0.9kg) |
| Humidity: | 65% ± 20% |
| Temperature: | 77°F ± 50° (25°C ± 10°C) |
| Packaging: | 10 per carton, 27lbs (13.2kg) |
| Packaging (RediDock): | 20 per carton |
| Faceplate Size: | Full length |
| FCC Specifications: | Meets or exceeds FCC Part 68, FCC Part 15 & UL 1459 Ref. |

| | |
|---------------------|--------------------------------|
| Safety Standard: | ETL and CE |
| | ADA/FCC Hearing Aid Compliant |
| | RoHS Environmentally Compliant |
| Signaling: | Standard 12 tone |
| Operating Voltage: | 24 to 52VDC (+/-) |
| Flash Timing: | .600 ms |
| Ringer Equivalence: | 0.6B |
| Handset: | .9ft. (2.25m) |
| Line Cord: | RJ25 Line Cord - 15ft. (4.5m) |

Cetis, Inc. Worldwide Headquarters

5025 Galley Road, Colorado Springs, CO 80915

North America Toll Free 1 800 462 9446 • Telephone +1 719 638 8821 • Fax +1 719 638 8815 • info@cetisgroup.com • cetisgroup.com



Scitec • Teledex • TeleMatrix